





• PLAIN TROLLEY



• GEARED TROLLEY



Model No.	Model No.	Cap.	Test load	Standard I-Beam			Max. distance between span	Track width adjustable Range	Min. Curve Radius	Net weight		Length of hand chain		
				Min-size	Max-size					kg	kg	M	kg	kg
Plain Trolley	Geared Trolley	Ton	Ton	mm			M	mm	M	kg	kg	M	kg	
PT-0.5	GT-0.5	0.5	0.75	H	W	t	3.0	62-128	0.8	5	5.4	2.5	8.9	9.4
				125 x 250	75 x 125	5.5 x 7.5								
PT-1	GT-1	1	1.5	125 x 250	75 x 125	5.5 x 7.5	2.5	62-128	1.0	7.3	7.8	2.5	11.1	11.7
				350 x 200	150 x 100	9.0 x 7.0	6.0							
PT-2	GT-2	2	3.0	180 x 350	100 x 150	6.0 x 9.0	3.0	88-154	1.3	12	12.6	2.5	16.3	17.1
				200 x 350	100 x 150	7.0 x 9.0	2.7							
PT-3	GT-3	3	4.5	200 x 350	100 x 150	7.0 x 9.0	2.7	87-153	1.5	19	19.8	2.5	23.3	24.3
				300 x 500	150 x 190	11.5 x 11.5	4.5							
PT-5	GT-5	5	7.5	250 x 500	125 x 190	10 x 11.5	4.0	106-194	1.5	30	31	2.5	34.3	35.6
				300 x 600	150 x 190	11.5 x 16	5.5							
PT-10	GT-10	10	15	300 x 600	150 x 190	11.5 x 16	2.0	125-310	2.7	135.5	145.5	2.5	150	162

Cap. (Ton)	A (mm)	B		C (mm)	E (mm)	D Track Width Adjustable Range(mm)
		Geared Trolley(mm)	Plain Trolley(mm)			
0.5	195	165	106	106	98	62-128
1	213	180	113	113	106	62-128
2	236	186	136	136	132	88-154
3	278	191	146	146	150	87-153
5	323	212	169	169	174	106-194